

Sustainability data sheet

ARDEX AF 495

Two Component PU Adhesive

Universally usable for parquet, floor coverings based on rubber and PVC. Very high resistance, for highly stressable areas (industry, sports facilities, heavy duty). High heat resistance for highly stressable areas, e.g. behind window facade. Moisture- and weather resistant, for application in damp and outdoor areas.

Emissions

According GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V., Düsseldorf)

EMICODE® EC 1^{PLUS} R,
very low emission



According Emission Classification of Building Materials

-

solvent-free

EPD (Environmental Product Declaration)

ARDEX AF 495 corresponds to FEICA EPD:

EPD-FEI-20150250-IBG1-EN

Technical Assessment

According GISBAU (TRGS 610, Technische Regeln für Gefahrstoffe):

GISCODE RU1 – solvent-free

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

www.ardex.de

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

kundendienst@ardex.de

www.ardex.de



ARDEX AF 495

Two Component PU Adhesive

Sustainable Building

Accordinging DGNB (Deutsche Gesellschaft für Nachhaltiges Bauen)

Version 2018

DGNB criteria ENV 1.2: Local environmental impact

ARDEX AF 495 can be classified as primers, primer coatings, putties and adhesives under wall and floor coverings (eg. Tiles, carpets, wooden floors, resilient flooring – except wallpaper).

ARDEX AF 495 has the GISCODE RU1 and is certified by EMICODE® EC 1^{PLUS} R, very low emission, based on GEV.

ARDEX AF 495 fulfills the requirements for highest Quality Level 4.

Version 2015

DGNB criteria ENV 1.2: Local environmental impact

ARDEX AF 495 can be classified as primers, primer coatings, putties and adhesives under wall and floor coverings (eg. Tiles, carpets, wooden floors, resilient flooring – except wallpaper).

ARDEX AF 495 is certified by EMICODE® EC 1^{PLUS} R, very low emission, based on GEV.

ARDEX AF 495 fulfills the requirements for highest Quality Level 4.

Accordinging LEED (Leadership in Energy and Environmental Design)

Version 4 (2014)

EQ: Low Emitting Materials

ARDEX AF 495 meets the requirements according EMICODE® EC 1^{PLUS} R, very low emission, based on GEV which are accepted by LEED.

ARDEX AF 495 meets the requirements and contributes to achieving one LEED point under EQ: Low Emitting Materials.

MR: Building Product Disclosure and Optimization – Environmental Product Declaration

ARDEX AF 495 corresponds to a model EPD by FEICA, which provides the evidence of a life cycle assessment (LCA) „cradle to gate“.

ARDEX AF 495 fulfills the requirements and contributes to achieving a LEED point under MR: Building Product Disclosure and Optimization – Environmental Product Declaration.

Version 2009

IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants

The permitted limit value in the category adhesives and sealants according SCAQMD Rule 1168 is 65 g/L. The VOC value of ARDEX AF 495 according SCAQMD Rule 1168 is < 65 g/L.

ARDEX AF 495 meets the requirements and contributes to achieving one LEED point under IEQ: Low Emitting Materials.

MR Credit 5.1 und 5.2: Regional Materials

Production site: 58453

Distance Production site – Project site < 800 km

Products that are used regionally within a 500 mile (800 kilometer) can be contributed to achieving one LEED point.

ARDEX GmbH
Friedrich-Ebert-Straße 45
58453 Witten
www.ardex.de

Tel.: +49 2302 664-511
Fax: +49 2302 664-298
kundendienst@ardex.de
www.ardex.de



ARDEX AF 495

Two Component PU Adhesive

Sustainable Building

Accordinging BREEAM-NOR (Building Research Establishment Environmental Assessment Methodology)

Version 2016

BREEAM criteria Hea 02 Indoor air quality

ARDEX AF 495 can be classified as Flooring Adhesives.

ARDEX AF 495 is certified by EMICODE® EC 1^{PLUS}, very low emission, based on GEV.

ARDEX AF 495 meets the requirements according BREEAM and contributes to achieving one credit under Hea 02 Indoor air quality.

Accordinging BREEAM (Building Research Establishment Environmental Assessment Methodology)

Version 2016

BREEAM criteria Hea 02 Indoor air quality

ARDEX AF 495 can be classified as Interior adhesives and sealants (including flooring adhesives). ARDEX AF 495 meets the requirements according Table 17: Emission criteria by product type and Table 18: Exemplary level emission criteria by product type.

ARDEX AF 495 is certified by EMICODE® EC 1^{PLUS}, very low emission, based on GEV.

ARDEX AF 495 meets the requirements according BREEAM and contributes to achieving one credit under Hea 02 Indoor air quality.

Notice: This data sheet has been compiled based on state-of-the-art technology and our experience. In spite of diligent treatment of all information ARDEX GmbH cannot guarantee the actuality or correctness of the published data. The interpretation of building certification criteria can differ and depend on the project and scope of application. The content of these data sheet does not manifest any legal relationship.

Additionally, the current information given in the Technical and the Material Safety Data Sheet have to be considered.

ARDEX GmbH
Witten, 19/01/2018

ARDEX GmbH
Friedrich-Ebert-Straße 45
58453 Witten
www.ardex.de

Tel.: +49 2302 664-511
Fax: +49 2302 664-298
kundendienst@ardex.de
www.ardex.de

