

# Sustainability data sheet

## ARDEX P 51 Priming dispersion

Primer, undercoating, bonding bridge and pore closing with water retardant effect.  
ARDEX P 51 can be diluted with water up to 3:1.

### Emissions

According GEV (Gemeinschaft  
Emissionskontrollierte  
Verlegewerkstoffe, Klebstoffe und  
Bauprodukte e.V., Düsseldorf)

solvent-free

### EPD (Environmental Product Declaration)

ARDEX P 51 corresponds to FEICA EPD:

**EPD-DBC-20220146-IBF1-EN**

### According BASTA

ARDEX P 51 is BASTA registered.

BASTA registration means that we can verify that this product meets agreed properties criteria regarding properties hazardous to the environment and health. See [www.bastaonline.se](http://www.bastaonline.se)



## Technical Assessment

According GISBAU (TRGS 610, Technische Regeln für Gefahrstoffe):

**GISCODE D1** – solvent-free dispersion installation products

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

[www.ardex.de](http://www.ardex.de)

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

[kundendienst@ardex.de](mailto:kundendienst@ardex.de)

[www.ardex.de](http://www.ardex.de)



# ARDEX P 51

Priming dispersion

## Sustainable Building

### Accordinging DGNB (German Sustainable Building Council)

#### Version 2023

#### DGNB criteria ENV 1.2: Local environmental impact

ARDEX P 51 can be categorized under Sealing coats, screed resins, waterproofing under tiles. ARDEX P 51 has the GISOCDE D1.

**ARDEX P 51 fulfils the requirements for Quality Level 1.**

### Accordinging LEED (Leadership in Energy and Environmental Design)

#### Version 4 (2014)

#### EQ: Low Emitting Materials

ARDEX P 51 does not meet the requirements according EMICODE® based on GEV which are accepted by LEED.

**ARDEX P 51 does not meet the requirements.**

#### MR: Building Product Disclosure and Optimization – Environmental Product Declaration

ARDEX P 51 corresponds to a model EPD by FEICA, which provides the evidence of a life cycle assessment (LCA) „cradle to gate“.

**ARDEX P 51 fulfils the requirements and contributes to achieving a LEED point under MR: Building Product Disclosure and Optimization – Environmental Product Declaration.**

#### Version 2009

#### IEQ Credit 4.1: Low Emitting Materials: Adhesives and Sealants

The permitted limit value in the category primers, sealings and undercoatings according SCAQMD Rule 1168 is 65 g/L. The VOC value of ARDEX P 51 according SCAQMD Rule 1168 is < 65 g/L.

**ARDEX P 51 meets the requirements and contributes to achieving one LEED point under IEQ: Low Emitting Materials.**

#### MR Credit 5.1 und 5.2: Regional Materials

#### Production site: 58453

Distance Production site – Project site < 800 km

Products that are used regionally within a 500 mile (800 kilometer) can be contributed to achieving one LEED point.

### Accordinging BREEAM-NOR (Building Research Establishment Environmental Assessment Methodology)

#### Version 2016

#### BREEAM-NOR criteria Hea 02 Indoor air quality

ARDEX P 51 is certified by M1 which is accepted as documentation.

**ARDEX P 51 meets the requirements according BREEAM-NOR and contributes to achieving one credit under Hea 02 Indoor air quality.**

ARDEX GmbH

Friedrich-Ebert-Straße 45

58453 Witten

www.ardex.de

Tel.: +49 2302 664-511

Fax: +49 2302 664-298

kundendienst@ardex.de

www.ardex.de



# ARDEX P 51

Priming dispersion

According Nordic Swan Ecolabelling

**ARDEX P 51 is listed in the database for building products that can be used in Nordic Swan Eco labelled buildings.**

**Notice:** This data sheet has been compiled based on state-of-the-art technology and our experience. In spite of diligent treatment of all information ARDEX GmbH cannot guarantee the actuality or correctness of the published data. The interpretation of building certification criteria can differ and depend on the project and scope of application. The content of these data sheet does not manifest any legal relationship. Additionally, the current information given in the Technical and the Material Safety Data Sheet have to be considered.

ARDEX GmbH  
Witten, 08/07/2024

ARDEX GmbH  
Friedrich-Ebert-Straße 45  
58453 Witten  
[www.ardex.de](http://www.ardex.de)

Tel.: +49 2302 664-511  
Fax: +49 2302 664-298  
[kundendienst@ardex.de](mailto:kundendienst@ardex.de)  
[www.ardex.de](http://www.ardex.de)

